



FC CE




Model (left side open)	Model (right side open)
K123	K123R

Benefits

- ▶ 1U 23" 4K LCD console drawer
- ▶ 3840 x 2160@60Hz native resolution / 1.07B colors (10-bit)
- ▶ 1920 x 1080 & 1920 x 1200 resolution support
- ▶ Display port 1.2 video input / USB KB/MS
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ Built-in dual stereo speakers
- ▶ One Man installation design
- ▶ Enhanced aesthetics with new molded front panel and 2-point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- Front USB hub port for device access
- HDMI 2.0 video input
- 3G / HD / SD-SDI Broadcast-grade input
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available



Product Specifications

Console Port

Video input attached 6ft DP cable	Display port 1.2
KB / MS bundled 6ft USB cable x 2	USB type A

LCD Panel

Panel size (diagonal)	23.8"
Native resolution	3840 x 2160@60Hz
Brightness (cd/m ²)	310
Contrast ratio (typ)	1000 : 1
Colors	1.07 Billion, 10-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	25
Dot pitch (mm)	0.13725
Display area (mm)	527.04H x 296.46V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	30,000

Video Option

Digital	HDMI	HDMI 2.0 / HDCP 2.2
---------	------	---------------------

Audio Option

Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 43W / Max. 54W
	Power saving mode	Max. 2W / Max. 18W
	Power button off	Max. 1W / Nil

Physical

Product (W x D x H)	Single console	442 x 690 x 44 mm 17.4 x 27.2 x 1.73 inch
	Console w/ KVM	442 x 750 x 44 mm 17.4 x 29.5 x 1.73 inch
Packing (W x D x H)	Single console / Console w/ KVM	595 x 910 x 140 mm 23.4 x 35.8 x 5.5 inch
	Net weight	Single console 15.3 kg / 33.7 lb
Gross weight	Console w/ KVM	16.1kg / 35.4 lb
	Single console	19.5 kg / 42.9 lb
Console w/ KVM		22 kg / 48.4 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance

Single console drawer	670 ~ 900 mm 26.4 ~ 35.4 inch
Console w/ KVM drawer	670 ~ 980 mm 26.4 ~ 38.6 inch


Compliance

EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant

K123 models w/ KVM

For right side open - Add **R** at the end of the model no.
sample : K123-801**KR**

4K 60Hz KVM	IP	Remote	8-port
	0	0	K123 - 801K





**** Resolution related to LCD specification**


4K KVM Cable	
CK - 6P (6 ft) DP KVM cable	CK - 6H (6 ft) HDMI KVM cable
Resolution	16:9 - max. 3840 x 2160
Support ** :	16:10 - max. 1920 x 1200
	4:3 - max. 1600 x 1200

Standard Keyboard

Ge G keyboard integrated with touchpad



Gb G keyboard integrated with trackball



Supporting layouts

America		United States
EMEA		United Kingdom
		Germany
		France
		Spain
		Italy
Asia		Japan
		Korea

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Mb Mac keyboard with trackball

Se S keyboard with touchpad

Sb S keyboard with trackball

