



FC CE

REACH

Model (left side open)	Model (right side open)
X124	X124R

Benefits

- ▶ 1U 24" LCD console drawer
- ▶ 1920 x 1200 **WUXGA** native resolution / 16.7M colors
- ▶ DVI-D + VGA video input / USB KB / MS
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ One Man installation design
- ▶ Enhanced aesthetics with new molded front panel and 2-point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- Front USB hub port for device access
- HDMI 1.3 video input
- 3G / HD / SD-**SDI** Broadcast-grade input
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available

Product Specifications

Console Port

Video input	VGA + DVI-D single link
KB / MS	USB interface
VGA console 6ft cable : CB-6A	Drawer end : DB-15 + USB type A x 2
or	Server end : DB-15 + USB type A x 2
DVI-D console 6ft cable : CX-6A	Drawer end : DVI-D + USB type A x 2
	Server end : DVI-D + USB type A x 2

LCD Panel

Panel size (diagonal)	24.1"
Native resolution	1920 x 1200
Brightness (cd/m ²)	300
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	14
Dot pitch (mm)	0.27
Display area (mm)	518.4H x 324V
Surface treatment	Anti-glare, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	30,000

Physical

Product (W x D x H)	Single console	442 x 700 x 44 mm 17.4 x 27.6 x 1.73 inch
	Console w/ KVM	442 x 800 x 44 mm 17.4 x 31.5 x 1.73 inch
Packing (W x D x H)	Single console /	595 x 910 x 140 mm
	Console w/ KVM	23.4 x 35.8 x 5.5 inch
Net weight	Single console	15.3 kg / 33.7 lb
	Console w/ KVM	16.1 kg / 35.4 lb
Gross weight	Single console	19.5 kg / 42.9 lb
	Console w/ KVM	22 kg / 48.4 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Mounting Distance

Single console drawer	660 ~ 890 mm 26 ~ 35 inch
Console w/ KVM drawer	660 ~ 970 mm 26 ~ 38.2 inch

Video Option

Digital	HDMI	HDMI 1.3 / HDCP 1.1
---------	------	---------------------

Audio Option

Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 33W / Max. 65W
	Power saving mode	Max. 2W / Max. 30W
	Power button off	Max. 1W / Nil

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance

EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant

X124 models w/ KVM


For right side open - Add **R** at the end of the model no.
sample : X124-MIP1624R

* **IP** console upgrade option for resolution support 1920 x 1080


** Resolution related to LCD specification

2K KVM	IP	Remote	8-port
	0	0	X124 - 801D

2K KVM Cable



CH - 6D (6 ft)
DVI-D KVM cable




CH - 6H (6 ft)
HDMI KVM cable

Resolution Support **: 16:9 - max. 2560 x 1440
16:10 - max. 1920 x 1200
4:3 - max. 1600 x 1200

DVI-D KVM	IP	Remote	12-port
	0	0	X124 - 1201D

DVI-D USB KVM Cable




Resolution Support **: 16:10 - max. 1920 x 1200
16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200


CI - 6 (6 ft)
CI - 15 (15 ft)

Cat6 Combo KVM	IP	Remote	8-port	16-port	32-port
	1	0	X124 - UIP802	X124 - UIP1602	X124 - UIP3202
	0	1	X124 - U802	X124 - U1602	X124 - U3202
	0	0	X124 - U801	X124 - U1601	X124 - U3201


Cat6 KVM Dongle




DG - 100P
DP - USB dongle




DG - 100H
HDMI - USB dongle



DG - 100SD
DVI - USB dongle



DG - 100S
VGA - USB dongle




DG - 100
VGA - PS/2 dongle


Resolution Support **: 16:10 - max. 1920 x 1200
16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200

DB-15 Matrix KVM	IP	Remote	8-port	16-port
	1	1	X124 - MIP813	X124 - MIP1613
	2	1	X124 - MIP824	X124 - MIP1624
	0	1	X124 - M802	X124 - M1602
	0	2	X124 - M803	X124 - M1603
	0	3	X124 - M804	X124 - M1604


DB-15 VGA USB KVM Cable



CB - 6 (6 ft)



CB - 10 (10 ft)



CB - 15 (15 ft)



Resolution Support **: 16:10 - max. 1920 x 1200
16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200

DB-15 Combo KVM	IP	Remote	8-port	16-port
	1	0	X124 - IP802	X124 - IP1602
	0	1	X124 - 802	X124 - 1602
	0	0	X124 - S801	X124 - S1601


DB-15 USB Hub KVM	IP	Remote	8-port	16-port
	1	0	X124 - IP802H	X124 - IP1602H
	0	1	X124 - 802H	X124 - 1602H
	0	0	X124 - 801H	X124 - 1601H

Standard Keyboard


Ge G keyboard integrated with touchpad










Gb G keyboard integrated with trackball



Supporting layouts

America  United States

EMEA  United Kingdom  Germany  France  Spain  Italy

Asia  Japan  Korea

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Se S keyboard with touchpad

Mb Mac keyboard with trackball

Sb S keyboard with trackball

